

```
!Current Configuration:  
!System Description "PowerConnect M6220, 2.2.0.3, VxWorks5.5.1"  
!System Software Version 2.2.0.3  
!System Operational Mode "Normal"  
!  
configure  
vlan database  
vlan 10,20,30,40,50,60,80,90,100  
exit  
hostname "BladeIO-A1"  
sntp unicast client enable  
sntp server 10.80.10.1  
clock summer-time recurring Usa offset 60 zone "PDT"  
clock timezone -8 minutes 0 zone "PST"  
stack  
member 1 1  
exit  
ip address 192.168.2.1 255.255.255.0  
ip domain-name puhsd.org  
ip name-server 10.71.1.10  
ip name-server 10.71.1.11  
  
username "root" password <redacted> level 15 encrypted  
!  
interface ethernet 1/g1  
switchport mode trunk  
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100  
switchport trunk allowed vlan remove 1  
exit  
!  
interface ethernet 1/g2  
switchport mode trunk  
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100  
switchport trunk allowed vlan remove 1  
exit  
!  
interface ethernet 1/g3  
switchport mode trunk  
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100  
switchport trunk allowed vlan remove 1  
exit  
!  
interface ethernet 1/g4
```

```
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g5
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g6
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g7
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1

exit
!
interface ethernet 1/g8
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g9
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g10
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g11
```

```
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g12
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g13
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g14
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1

exit
!
interface ethernet 1/g15
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g16
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
!
interface ethernet 1/g17
channel-group 1 mode auto
exit
!
interface ethernet 1/g18
channel-group 1 mode auto
exit
```

```
!
interface ethernet 1/g19
channel-group 1 mode auto
exit
!
interface ethernet 1/g20
channel-group 1 mode auto
exit
!
interface port-channel 1
switchport mode trunk
switchport trunk allowed vlan add 10,20,30,40,50,60,80,90,100
switchport trunk allowed vlan remove 1
exit
interface out-of-band
ip address 10.80.10.11 255.255.254.0 10.80.10.1
exit
exit
```