Hadoop Basics with InfoSphere BigInsights

Unit 4: Hadoop Administration



Catalog Number

© Copyright IBM Corporation, 2013

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

LAB 1	HADO		INISTRATION	
	1.1	MANAG	SING A HADOOP CLUSTER	5
		1.1.1	ADDING/REMOVING A NODE FROM THE CLUSTER	5
		1.1.2	SETTING UP MASTER/SLAVE NODES	ERROR! BOOKMARK NOT DEFINED.
		1.1.3	ADDING A NODE FROM WEB CONSOLE	Error! BOOKMARK NOT DEFINED.
		1.1.4	ADDING A NODE FROM THE TERMINAL	
		1.1.5	REMOVING A NODE	
		1.1.6	HEALTH OF A CLUSTER	
		1.1.7	VISUAL HEALTH CHECK	
		1.1.8	DFS DISK CHECK	
	1.2	Hadoo	P ADMINISTRATION	
		1.2.1	ADMINISTERING SPECIFIC SERVICES	
		1.2.2	CONFIGURING HADOOP DEFAULT SETTINGS	
		1.2.3	INCREASING STORAGE BLOCK SIZE	
		1.2.4	LIMIT DATA NODES DISK USAGE	
		1.2.5	CONFIGURING THE REPLICATION FACTOR	
	1.3	IMPORT	TING LARGE AMOUNTS OF DATA	ERROR! BOOKMARK NOT DEFINED.
		1.3.1	MOVING DATA TO AND FROM HDFS	ERROR! BOOKMARK NOT DEFINED.
		1.3.2	HADOOP COMMANDS THROUGH TERMINAL	ERROR! BOOKMARK NOT DEFINED.
		1.3.3	HADOOP COMMANDS THROUGH WEBCONSOLE	ERROR! BOOKMARK NOT DEFINED.
	1.4	SUMMA	ιRΥ	

Lab 1 Hadoop Administration

IBM's InfoSphere BigInsights 3.0 Enterprise Edition enables firms to store, process, and analyze large volumes of various types of data using a wide array of machines working together as a cluster. In this exercise, you'll learn some essential Hadoop administration tasks from expanding a cluster to ingesting large amounts of data into the Hadoop Distributed File System (HDFS).

After completing this hands-on lab, you'll be able to:

- Manage a cluster running BigInsights to add or remove nodes as necessary
- Cover essential Hadoop administration tasks such as expanding disk space and how to start and stop services

Allow 60 minutes to 90 minutes to complete this lab.

This version of the lab was designed using the InfoSphere BigInsights Cluster Capable Quick Start Edition and tested on BigInsights 3.0. Throughout this lab you will be using the following account login information:

NOTE: Make sure to get the Cluster Capable Quick Start Edition

	Username	Password
VM image setup screen	root	password
Linux	biadmin	biadmin

For this lab all Hadoop components should be up and running. If all components are running you may move on to Section 2 of this lab. Otherwise please refer to Hadoop Basics Unit 1: Exploring Hadoop Distributed File System Section 1.1 to get started. (All Hadoop components should be started)

1.1 Managing a Hadoop Cluster

In this section you will learn how to:

- Add and remove nodes through Web Console, and Terminal
- Check the health of the cluster and individual nodes within that cluster
- Perform checks on the disk and storage of the HDFS

Typical Hadoop clusters rely on being able to use multiple cheap computers/devices as nodes working together as a Hadoop cluster. Because of this, and the way in which hardware and hard disk drives operate from a mechanical point, the hardware is bound to fail over the years – which hadoop handles efficiently by replicating the data across the various nodes (3-node replication by default).

1.1.1 Prepare your environment for a multi-node cluster

So far you have been working with just a single node cluster. To add a second node to the cluster, you need to have a second VMWare image. For clarification purposes, the existing image will be referred to as the master image.

- ___1. Unzip the image that you downloaded to a different directory. Boot it and go through the same process of accepting the licenses that you did for the Master image. Specify the same password for *root* and *biadmin* for the child image as you did for the Master image.
- ____2. Once your child image boots up, log in with a username of **biadmin**.
- __3. For a node to be added to a BigInsights cluster, BigInsights cannot be installed. You need to uninstall BigInsights on the child image. Double click the Clean Local BI icon on the desktop to uninstall BigInsights.



Child image

- __4. You need to update the hostname on the child image. (It currently has the same hostname as the master.) You also need to update the /etc/hosts file so the child image can communicate with the master image. Right click the desktop and select **Open in Terminal.**
 - __a. Switch to root

su -

___b. Edit /etc/HOSTNAME

gedit /etc/HOSTNAME

_c. Update the hostname from *bivm.ibm.com* to **bivm2.ibm.com**. Save your work and close the editor.



____d. From the command line execute

hostname bivm2.ibm.com

- ___e. Execute *hostname* without any parameters to verify that the hostname was changed.
- ___f. Get the ipaddress from the master image. On the master image, right-click the desktop, select **Open in Terminal.** Then from the command line execute:

su -

ifconfig

__g. On the child image, edit the /etc/hosts file. (gedit /etc/hosts) Change the hostname to bivm2.ibm.com bivm2 Then add the ipaddress and hostname from the master. Save your work and close the editor.

The following is an example. In this case, the ipaddress for the master was **192.168.70.202** and the ipaddress for the child was **192.168.70.201**.

🖹 hosts 🗙	
127.0.0.1	localhost.localdomain localhost
192.168.70	.202 bivm.ibm.com bivm
192.168.70	.201 bivm2.ibm.com bivm2

Master image

__5. On the master image, switch user to root. Then edit **/etc/hosts** and add the hostname and ipaddress for the child image. Save your work and close the editor.

1.1.2 Adding/Removing a node from the cluster

One of the key parts of managing a Hadoop cluster is being able to scale the cluster with ease, adding and removing nodes as needed. Adding a node can be done through a range of methods, of which we

will cover adding from a BigInsights Console, and from a terminal. Each of these methods can achieve the same results.

Before proceeding with adding a node, you should first verify that you can access the node you are trying to add. This can be done by simply "sshing" the given node(s) as follows.

- ___6. On the *master* image, open a terminal window by right-clicking the desktop and select **Open in Terminal.**
- ___7. Type the following ssh command to make sure that you have connectivity between the master and the child images:

ssh root@bivm2.ibm.com

When doing ssh on a new IP you will get an authenticity message:

```
The authenticity of host 'bivm2.ibm.com (192.168.70.201)' can't be established.
RSA key fingerprint is 29:2f:72:9f:f4:97:16:89:cf:d9:cc:09:d3:16:d9:bf.
Are you sure you want to continue connecting (yes/no)?
```

Go ahead and type **yes**, you will then get a warning:

```
Warning: Permanently added 'bivm2.ibm.com,192.168.70.201' (RSA) to the list of known hosts.
```

Enter the password for root on the child image.

If you are successful in the above steps then your terminal should look similar to the image below:

▼ biadmin@bivm:~/Desktop _ [
File Edit View Terminal Help	
<pre>biadmin@bivm:~/Desktop> ssh root@bivm2.ibm.com The authenticity of host 'bivm2.ibm.com (192.168.70.201)' can't be established RSA key fingerprint is eb:35:c3:3d:bb:27:4e:0d:fe:24:fe:19:e2:ed:36:80. Are you sure you want to continue connecting (yes/no)? yes Warning: Permanently added 'bivm2.ibm.com,192.168.70.201' (RSA) to the list of nown hosts. Password: Last login: Thu Apr 10 16:45:42 2014 bivm2:~ # exit logout Connection to bivm2.ibm.com closed.</pre>	• • •

8. Exit the ssh connection.

exit

1.1.3

One of the great features of IBM's Infosphere BigInsights, is the web console. The web console provides an interface to not only the data in HDFS, but also a user-friendly way for performing the tasks associated with simple and advanced hadoop scripts as well as extensive visualizations.

All of the following steps will be done on your **Master node**.

BigInsights services must be started.

- ___1. First start the BigInsights components. Right click the desktop of the master image and select **Open in Terminal.** (These steps that start the BigInsights components assume that those components are not currently started. If they are still running from the previous exercise, then you do not have to restart them.)
- _2. Start the BigInsight Components. You could use the *Start BigInsights* icon on the desktop. But this icon is only available with the Quick Start Edition image. When you install BigInsights, that icon will not be there. So let's use the technique that you will use in real-life. At the command line type:

\$BIGINSIGHTS_HOME/bin/start-all.sh

__3. Launch the Web Console by clicking on the BigInsights WebConsole icon. (Once again, this icon is only available with the Quick Start Edition image. In real-life you would open Firefox and specify a URL of <u>http://<hostname>:8080</u> (where <hostname> is the host where the console runs.)



__4. For the Quick Start Edition, you will need to use the credentials to log into the BigInsights Console. Log in with a username of **biadmin** and specify the password that you assigned to *biadmin* when you configured the image. You should now be at the Welcome Page

IBM I	IBM InfoSphere BigInsights Quick Start Edition (for Non-Production Environment) Welcome biadmin [Log out [Help								IBM.
Welcome	Dashboard	Cluster Status	Files	Applications	Application Status	BigSh	eets		
Understa Lean Unde	and IBM's Big Data 1 n about biginsights erstand the tools for	ools analyzing data at	4		4.		wick Li	nks Download client library and development software Enable your Eclipse development environment for BigInsights application development	
Tasks							-	Access secure cluster servers	
4	Accelerate machine If you have installed o analytics	log, social, and telec ne of the IBM accelera	ommunicati tors, you can	ons analytics run applications to	jump-start your big data		-	Run Big SQL Queries	
-	Create a dashboard Create a dashboard to	monitor your applicat	ion			Le	earn N	lore	
T	Explore and update Explore your data set	data using sheets to discover, analyze, a	and visualize	your data.			B	Accelerator demos and documentation	
-	Run an application Run an application on	ce, immediately.					*	Infosphere BigInsights Information Center	
-	Deploy or remove an Deploy an application	on a cluster, or remov	e an applicati	on from a cluster.			ø* •	Infosphere Streams Information Center Communities and forums	
-	Add and remove no Add or remove nodes services.	des and services and service from your	r cluster, in ac	Idition to starting, st	opping, and managing		4	Support IBM big data on the Web	
40	Manage alerts Create rules, manage	existing rules, and act	tivate rules.					-	

__5. Click on the Cluster Status tab.



__6. Click on Nodes then click the Add nodes button

Welcome Dash	board	Cluster	Status	Files	Application
Monitor Services	Mana	ige Alerts	Log Se	ettings	Backup and
Nodes		O 1		No	des
Map/Reduce		SRun	ning	<	Add nodes
HDFS	📀 Running				
Alert		SRun	ning		No filter a
Big SQL		📀 Run	ning	-	ino inter d

____7. Enter the hostname or the IP address of the node to be added to the cluster. This node must be online and reachable. (You can add multiple nodes at the same time.)

Type the password for root. This is for root on the nodes to be added. In this exercise it will be the password for root on the child image.

Click on the **ok** button and then *accept* on the subsequent popup.

∗ Hosts: ℗	bivm2.ibm.com
	ii.
] Hosts are	e public 🕐
ne root user stribute SSH	will be used to create the BigInsights administrative user and Heys.
Root	•••••
Root password: The rack nam ralidate the ra The rack can jame/rack-na	e may be used as a prefix to the host. BigInsights Console does not ack information. be specified as an arbitrary path in the following format: /top-switch- ume. Example: /default-rack

An add node progress bar will appear. Be patient as this may take some time.

Resolve Hosts		
	70%	

___8. A Node Availability window displays the specified nodes and their status.Click **Accept** to proceed.

ck Cancel to return to the Nodes page with the Modify to return to the Add Nodes dialog	out adding any nodes. to modify the information
ck Modify to return to the Add Node's dialog	to modify the information
ully Qualified Domain Name	Status
bivm2.ibm.com	Available

__9. It will take a few seconds for the nodes to appear up in the Node list. After having added the node, then you must then specify the services that are to run on that node. Click on **Add services**.

dd nodes	Add services	Remove servic	e services Hemove nodes	
	Host			Status
No filter a	applied			
	bivm.ibm.com		🕑 🚺 Ho	st is running
	bivm2.ibm.com		🕑 🔢 Ho	st is running

___10. For Services select DataNode/TaskTracker, and for Nodes select bivm2.ibm.com and then click Save.

Services	DataNode/TaskTracker	
	HttpFS	
	HBase Master	
	HBase Region Server	
	Zookeeper	
Nodes	bivm.ibm.com (public)	P
	bivm2.ibm.com (private)	

___11. You will now have a progress bar. This may take some time so be patient. At this point the necessary BigInsights code is being copied to and installed on the selected node(s).

Add Services		
	10%	

___12. After some time, you will get this window. Click **OK**.

Name	Service	Status
bivm2.ibm.com	DataNode/TaskTracker	Operation finished successfully.[NFO]

You have now successfully added 1 child node to your cluster. The method which we just used is one of the simplest manners to expand your cluster, however, we will cover another very useful method below. You can quickly see which nodes are running by navigating back to the *Cluster Status* tab in your BigInsights console.

Nodes						
Add nodes	Add services	Remove services	Remove nodes	Refresh Interval: 15 seconds		
Host Status			Status	Roles		
😒 No filter	applied					
bivm.ibm.com		0	1 Host is running	secondarynamenode, zookeeper-client-port, bigsql-server, hive-v		
bivm2.ibm.com		0	🚺 Host is running	monitoring, datanode, tasktracker		

1.1.4 Adding a node from the Terminal Command Line

You may also choose to add a node from the terminal. This can prove useful for a variety of different scenarios, such as real-time error logs if a node is not able to add successfully. Additionally, if you are not running the 'Console' service within BigInsights, or are using a remote connect program such as Putty to ssh into your cluster- this proves very useful. REMEMBER to update the /etc/host file for the master node and new child node.

You may not have the resources on your PC to run three images. If you do not, then you can skip this section.

To do this section, you must unzip the download Quick Start image to a new directory. You must go through the same steps that you did in section 1.1.1 in order to remove the BigInsights code from this new child image, update the hostname to **bivm3.ibm.com**, and update the /etc/hosts file on all three images so that all three images can access each other.



- ___1. On the master image, right click the desktop and select **Open in Terminal**.
- ___2. Change directory to **\$BIGINSIGHTS_HOME/bin** and execute the following:

addnode.sh <component> <IP_Addr OR Hostname>,password

▼ biadmin@bivm:bm/biginsights/bin _ □	×
File Edit View Terminal Help	
Directory: /home/biadmin/Desktop	
Fri Apr 11 14:06:43 EDT 2014	
biadmin@bivm:~/Desktop> cd \$BIGINSIGHTS_HOME/bin	
biadmin@bivm:/opt/ibm/biginsights/bin> addnode.sh hadoop bivm3.ibm.com,password	
[INFO] DeployCmdline - [IBM InfoSphere BigInsights QuickStart Edition]	
[INFO] HdmUtil - Install configuration has changed in the system, reloading	
[INFO] org.apache.hadoop.conf.Configuration.deprecation - mapred.job.tracker.htt	t
p.address is deprecated. Instead, use mapreduce.jobtracker.http.address	
[INFO] org.apache.hadoop.conf.Configuration.deprecation - mapred.task.tracker.ht	t
tp.address is deprecated. Instead, use mapreduce.tasktracker.http.address	
[INFO] Prerequisite check - Reset ulimits for biadmin	

<component> in our case is hadoop. IP_Addr is the IP address of the new node you want to add, and Hostname is the name you have for the node in your /etc/hosts file. The password will be root's password on the child system. (And note that there is no space between the comma and root's password.)

Adding a node through the terminal will take some time. After the node has been added, you will get a message at the end:

```
[INFO] DeployManager - biginsights.properties unchanged, monitoring is already d
isabled
[INFO] DeployManager - Add hadoop nodes; SUCCEEDED components: [hadoop]; Consume
s : 421505ms
biadmin@bivm:/opt/ibm/biginsights/bin>
```

You have now successfully added a second node. You now have 2 child nodes.

No filter applied		
bivm.ibm.com	🖉 🛐 Host is running	secondarynamenode, zookeeper-client-port, bigsql-server, hive-v
bivm3.ibm.com	🛇 🛐 Host is running	monitoring, datanode, tasktracker
bivm2.ibm.com	🖉 🛐 Host is running	monitoring, datanode, tasktracker

1.1.5 Removing a node

Removing a node is as simple as adding a node, as the steps are very similar. We will show how to remove a node through the terminal in a quick manner. If a node has more than one service running, such as hadoop or zookeeper, the specific service to be removed may be specified in the script. Or if no service is specified the node is removed completely. REMEMBER to update the /etc/hosts file before removing

- ___1. On the master image, open a terminal.
- __2. You can remove a node by executing the following script. The --f parameter says not to worry that some file chunks will not have a full set of replicas. Once again, you need to change to the \$BIGINSIGHTS_HOME directory.

removenode.sh --f <IP_Addr OR Hostname>

Where IP_Addr is the IP address of the Slave node you want to remove and Hostname is the host name of the Slave node you wish to remove.

▼ biadmin@bivm:pt/ibm/biginsights	
File Edit View Terminal Help	
Directory: /home/biadmin/Desktop	
Fri Apr 11 15:01:07 EDT 2014	
biadmin@bivm:~/Desktop> cd \$BIGINSIGHTS_HOME	
biadmin@bivm:/opt/ibm/biginsights> removenode.shf bivm3.ibm.com	
[INFO] DeployCmdline - [IBM InfoSphere BigInsights QuickStart Edition]	
[INFO] HdmUtil - Install configuration has changed in the system, reloading.	
[INFO] DeployManager - Stop monitoring agents on nodes:[bivm3.ibm.com]	
[INFO] Deployer - Stop monitoring agents on [bivm3.ibm.com]	
[INFO] Deployer - Monitoring agent is stopped on bivm3.ibm.com already.	
[INFO] Deployer - monitoring service stopped	
[INFO] Progress - RemoveNodes httpfs	
[INFO] @bivm3.ibm.com - This node is not in httpfs cluster	
[INFO] Progress - 16%	
[INFO] Progress - RemoveNodes oozie	
le e coñ con la construcción de la	
You should see this at the end:	

```
[INFO] DeployManager - Cluster nodes removed [bivm3.ibm.com]
[INFO] DeployManager - RemoveNodes; SUCCEEDED components: [httpfs, oozie, hbase,
hadoop, zookeeper, monitoring]; Consumes : 64061ms
biadmin@bivm:/opt/ibm/biginsights>
```

___3. To verify that the node is now removed you can run the listnode.sh script.

listnode.sh

▼ biadmin@bivm:pt/ibm/biginsights _ □ X
File Edit View Terminal Help
biadmin@bivm:/opt/ibm/biginsights>
biadmin@bivm:/opt/ibm/biginsights> listnode.sh
[INFO] DeployCmdline - [IBM InfoSphere BigInsights QuickStart Edition]
[INFO] DeployManager - All cluster nodes: [bivm.ibm.com, bivm2.ibm.com]
[INFO] HdmUtil - Install configuration has changed in the system, reloading
[INFO] DeployManager - alert nodes: {bivm.ibm.com}
[INFO] DeployManager - bigsgl nodes: {biym.ibm.com}
[INFO] DeployManager - catalog nodes: {bivm.ibm.com}
[INFO] DeployManager - console nodes: {bivm.ibm.com}
[INFO] DeployManager - hadoop nodes: {bivm.ibm.com=[namenode, secondarynamenode,
jobtracker, datanode, tasktracker], bivm2.ibm.com=[datanode, tasktracker]}
[INFO] DeployManager - hbase nodes: {bivm.ibm.com=[master, regionserver]}
[INFO] DeployManager - hbase backup nodes: {bivm.ibm.com}
[INFO] DeployManager - hive nodes: {bivm.ibm.com=[hive, hive-web-interface, hive
-server2], bivm2.ibm.com}
[INFO] DeployManager - httpfs nodes: {bivm.ibm.com=[httpfs-server]}
[INFO] DeployManager - jagl nodes: {biym.ibm.com. biym2.ibm.com}
[INFO] DeployManager - oozie nodes: {biym.ibm.com}
[INFO] DeployManager - pig nodes: {biym.ibm.com. biym2.ibm.com}
[INFO] DeployManager - zookeeper nodes: {biym.ibm.com=[1]}
[INFO] DeployManager - List node: SUCCEEDED components: [alert, bigsgl, catalog.
console, hadoop, hbase, hbase backup, hive, httpfs, jagl, oozie, pig, zookeeper
1: Consumes : 988ms
biadmin@bivm:/opt/ibm/biginsights>

1.1.6 Health of a Cluster

Servers, machines, and disk drives are all prone to a physical failure over time. When running a large cluster with dozens of nodes, it is crucial to over time maintain a constant health check of hardware and take appropriate actions when necessary. BigInsights 2.1.2 allows for a quick and simple way to perform these types of health checks on a cluster.

1.1.7 Visual Health Check

You can visually check the status of your cluster by following these simple steps:

___1. Open a BigInsights Console window by clicking the Web console icon.



____2. You should now be in the Welcome page. Click on the Cluster Status tab.



From here you can check the status of your nodes

Nodes	©2	Nodes				
Map/Reduce	Running	Add nodes	Add services	Remove services	Remove nodes	
DFS	S Running	Host			Status	
Big SQL	Running	🗢 No filter a	pplied node1	📀 🛐 Host	is running	
Catalog	Running	bivm.ibm.com		🥝 🛐 Host	🥝 🛐 Host is running	
Base	Running					
live	Running	4				
IttpFS	Running	-				
Monitoring	⊗Unavailable					
lozie	Running					
Zookeeper	Bunning					

You can also check the status of each component.

Nodes	O2
Map/Reduce	Running
HDFS	Running
Alert	📀 Running
Big SQL	📀 Running
Catalog	📀 Running
HBase	📀 Running
Hive	📀 Running
HttpFS	📀 Running
Monitoring	😵 U navailable
Oozie	Running
Zookeeper	Running

1.1.8 DFS Disk Check

There are various ways to monitoring the DFS Disk, and this should be done occasionally to avoid space issues which can arise if there is low disk storage remaining. One such issue can occur if the "hadoop healthcheck" or heartbeat as it is also referred to sees that a node has gone offline. If a node is offline for a certain period of time, the data that the offline node was storing will be replicated to other nodes (since there is a 3node replication, the data is still available on the other 2 nodes). If there is limited disk space, this can quickly cause an issue.

___1. From a terminal window you can quickly access the dfs report by entering the following command:

hadoop dfsadmin -report



1.2 Hadoop Administration

After completing this section, you'll be able to:

- Start and stop individual services to best optimize the cluster performance
- Change default parameters within Hadoop such as the HDFS Block Size
- Manage service-specific slave nodes

1.2.1 Administering Specific Services

A single node can have a wide variety of services running at any given time, as seen in the screenshot below. Depending on your system and needs, it may not always be necessary to have all of the services running, as the more services running the more resources and computing power is being consumed by them.



Stopping specific services can be done easily through the terminal, as well as through the web console. For the purpose of this lab, we will stop the 2 services, *hadoop* and *console* which should have been previously started.

- __1. Open a terminal window.
- ___2. Stop the hadoop and console services by entering the following:

stop.sh hadoop console

E	admin@bigdata:/opt/ibm/biginsights/bin
Elle Edit View Jerminal Tabs Help	
[biadmin@crbigdata ~]S cd SBIGINSIGHTS HOME/bin	1
[biadmin@crbigdata bin]\$./stop.sh hadoop conse	ole
[INFO] Progress - Stop console	
[INFO] Deployer - stopping pigserver	
[INFO] Deployer - no pigserver to stop	
[INFO] Deployer - Stopping BigInsights Manageme	ant Console
[INFO] Deployer - Server waslp-server stopped.	
[INFO] Progress - 50%	
[INFO] Progress - Stop hadoop	
[INFO] @bigdata - jobtracker stopped	
[INFO] Progress - 60%	
[INFO] @bigdata - tasktracker stopped	
[INFO] Progress - 63%	
[INFO] @192.168.44.129 - tasktracker already st	copped
[INFO] Progress - 65%	
[INFO] @bigdata - secondarynamenode stopped	
[INFO] Progress - 70%	
[INFO] Progress - 80%	
[INFO] @bigdata - namenode stopped	
[INFO] Progress - 85%	
[INFO] @bigdata - datanode stopped	
[INFO] Progress - 88%	
[INFO] @192.168.44.129 - datanode already stopp	oed
[INFO] Progress - 90%	
[INFO] Progress - 100%	
[INFO] DeployManager - Stop; SUCCEEDED component	its: [console, hadoop]; Consumes : 25094ms
[biadmin@crbigdata bin]\$	and (territories and an and the state of a state of the

The output should look similar to the image above.

1.2.2 Configuring Hadoop Default Settings

Configuration files for Hadoop are split into three files.

- core-site.xml covers the Hadoop system
- hdfs-site.xml covers HDFS specific configuration parameters
- mapred-siet.xml covers MapReduces specific configuration parameters

These configuration files reside in the \$BIGINSIGHTS_HOME/hadoop-conf directory. Since there are multiple nodes in the cluster, when you change a configuration parameter, those changes need to be made on all nodes in the cluster, where it is appropriate. To automate this process, BigInsights includes a script, *syncconf.sh* that synchronizes the changes. For this to work, you do not modify the actual configuration files, but rather the *staging* configuration files. These files are located in the \$BIGINSIGHTS_HOME/hdm/hadoop-conf-staging directory.

1.2.3 Increasing Storage Block Size

There are certain attributes from Apache Hadoop which are imported, and some have been changed to improve performance. One such attribute is the default block size used for storing large files.

Consider the following short example. You have a 1GB file, on a 3-node replication cluster. With a blocksize of 128MB, this file will be split into 24 blocks (8 blocks, each replicated 3 times), and then stored on the Hadoop cluster accordingly by the master node. Increasing and decreasing the block size can have very specific use-case implications, however for the sake of this lab we will not cover those Hadoop specific questions, but rather how to change these default values.

Hadoop uses a standard block storage system to store the data across its data nodes. Since block size is slightly more of an advanced topic, we will not cover the specifics as to what and why the data is stored as blocks throughout the cluster.

The default block size value for IBM BigInsights 2.1.2 is currently set at 128MB (as opposed to the Hadoop default of 64MB as you will see in the steps below). If your specific use-case requires you to change this, it can be easily modified through Hadoop configuration files.

- __1. When making any Hadoop core changes, it is good practice (and a requirement for most) to stop the services you are changing before making any necessary changes. For the block size, you must stop the "Hadoop" and "Console" services before proceeding if you have not done so in the previous steps, and re-start them after you have made the changes.
- ____2. Move to the directory where Hadoop staging configuration files are stored

cd \$BIGINSIGHTS_HOME/hdm/hadoop-conf-staging

ls

▼ biadmin@bivm:adoop-c	onf-staging		_ 🗆 X
File Edit ∨iew Terminal	Help		
Directory: /opt/ibm/big	insights/hdm/hadoop-conf-sta	ging	*
Fri Apr 11 15:45:06 EDT	2014		
biadmin@bivm:/opt/ibm/b	iginsights/hdm/hadoop-conf-s	taging> ls	
capacity-scheduler.xml	hadoop-metrics2.properties	masters	
configuration.xsl	hadoop-policy.xml	slaves	
console-site.xml	hdfs-site.xml	ssl-client.xml.example	
core-site.xml	ibm-hadoop.properties	ssl-server.xml.example	
excludes	includes	taskcontroller.cfg	
fair-scheduler.xml	log4j.properties	zk-jaas.conf	
flex-scheduler.xml	mapred-queue-acls.xml		
hadoop-env.sh	mapred-site.xml		
biadmin@bivm:/opt/ibm/b	iginsights/hdm/hadoop-conf-s	taging>	

__3. Within this directory, you will see a file named "hdfs-site.xml", one of the site-specific configuration files, which is on every host in your cluster.

gedit hdfs-site.xml

__4. Navigate to the property called *dfs.block.size*, and you will see the value is set to 128MB, the default block size for BigInsights. For the purpose of this lab, we will not change the value.



1.2.4 Configuring the replication factor

- ___1. Navigate to the property named *dfs.replication*.
- __2. The current default replication factor will depend on the number of DataNodes that you have in your cluster. If you only have one, then the value is 1. If you have two DataNodes, then you will see a value of 2. For three or more DataNodes, the value will be 3. You can overwrite the default value by adding the following lines to this file (hdfs-site.xml). The value will be the number of your choice.



1.2.5 Limit DataNodes disk usage

__1. Navigate to the property named dfs.datanode.du.reserved. This value represents reserved space in bytes per volume. HDFS will always leave this much space free for non-dfs use.

```
<property>
<name>dfs.secondary.http.address</name>
<value>bigdata:50090</value>
</property>
<name>dfs.datanode.du.reserved</name>
<value>6012954214</value>
</property>
<name>dfs.hosts</name>
<value>/opt/ibm/biginsights/hadoop-conf/includes</value>
</property>
</configuration>
```



NOTE: This configuration file is site-specific which means it only is affective for a node this file belongs to. Read-only default configuration is stored at \$BIGINSIGHTS_HOME/IHC/src/hdfs/hdfs-default.xml

_2. For the purpose of this lab, we will not save this configuration change. This part of the lab is just to let you browse how to change some of the configuration values when you need it later on. However, in real-life, once you have made changes to this file, you would then run the *syncconf.sh* script to synchronize this file across all appropriate nodes in the cluster.

1.3 Summary

Congratulations! You have now experience some common tasks of hadoop administrations.



© Copyright IBM Corporation 2013.

The information contained in these materials is provided for informational purposes only, and is provided AS IS without warranty of any kind, express or implied. IBM shall not be responsible for any damages arising out of the use of, or otherwise related to, these materials. Nothing contained in these materials is intended to, nor shall have the effect of, creating any warranties or representations from IBM or its suppliers or licensors, or altering the terms and conditions of the applicable license agreement governing the use of IBM software. References in these materials to IBM products, programs, or services do not imply that they will be available in all countries in which IBM operates. This information is based on current IBM product plans and strategy, which are subject to change by IBM without notice. Product release dates and/or capabilities referenced in these materials may change at any time at IBM's sole discretion based on market opportunities or other factors, and are not intended to be a commitment to future product or feature availability in any way.

IBM, the IBM logo and ibm.com are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.



Please Recycle

IBM Software