

vmware®

Networking & Security Business Unit



# NSX for vSphere

## Requirements Checklist

for  
<Customer>

Prepared by  
<VMware Team>  
<email-address@vmware.com>

## Version History

Date	Rev.	Author	Description	Reviewers
7 Jul 2013	1.0	Ray Budavari	Initial Document	
22 Jul 2013	1.1	Ray Budavari	Refresh Build Numbers	
24 Nov 2013	1.2	Ray Budavari	GA update	
8 Jan 2014	1.3	Ray Budavari	6.0.1 update	
18 Mar 2014	1.4	Ray Budavari	6.0.2 update	
3 Jul 2014	1.5	Ray Budavari	6.0.X updates	
3 Oct 2014	1.6	Ray Budavari	6.1.1 update	

© 2014 VMware, Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. This product is covered by one or more patents listed at <http://www.vmware.com/download/patents.html>.

VMware is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

VMware, Inc.  
3401 Hillview Ave  
Palo Alto, CA 94304  
[www.vmware.com](http://www.vmware.com)

# Contents

- 1. Overview ..... 5
- 2. General Requirements ..... 6
- 3. NSX vSphere Topologies..... 7
- 4. Hardware Requirements ..... 9
- 5. Software Requirements ..... 11
- 6. Network Requirements ..... 14
- 7. Resource Requirements ..... 17
- 8. Sample Timeline ..... 18

## List of Tables

Table 1. NSX Hardware Requirements ..... 9

Table 2. NSX Software Requirements ..... 11

Table 3. vCenter Server ..... 12

Table 4. ESXi Hosts ..... 12

Table 5. NSX for vSphere Components ..... 12

Table 6. Management VM Sizing ..... 13

Table 7. NSX Network Requirements ..... 14

Table 8. Network Parameters ..... 15

Table 9. NSX for vSphere Port & Protocol Requirements ..... 16

Table 10. Customer Resources ..... 17

Table 11. VMware NSBU Resources ..... 17

Table 12. Timelines ..... 18

## 1. Overview

This document details the requirements for a PoC evaluation of the VMware NSX platform to provide network and security virtualization in a vSphere environment. The primary goal of the PoC is to gain hands on familiarity with the capabilities of NSX and understand how the product can be leveraged to address business and technical requirements. In addition customers will engage with VMware to agree on a set of use cases for the NSX PoC.

The scope of the PoC will be based on these jointly defined use cases. Preparation of the environment based on the information in this document is essential for a successful NSX evaluation.


## 2. General Requirements

During any onsite work, the following items should be available:

- Conference room
- Whiteboard for knowledge transfer
- Projector for training sessions
- If required due to security requirements, a desktop or laptop with accessible to the evaluation environment

### 3. NSX vSphere Topologies

The NSX PoC evaluation will demonstrate the following physical network and compute topology:



**Figure 1 – VMware NSX Physical Topology**

Both Layer 3 or Layer 2 transport networks are fully supported by NSX, however to most effectively demonstrate the flexibility and scalability of network virtualization a L3 topology with different routed networks for the Compute and Management/Edge Clusters is recommended.

It is also recommended that Management & Edge Clusters are separated if sufficient hardware is available, as this aligns with the best practices for deployment of NSX.

The logical network topology will depend on the environment and workloads plus the features being evaluated, although a typical example based on the capabilities of NSX and the classical N-Tier application model is displayed below:




Figure 2 – VMware NSX Logical Topology

Another common application deployment model is to collapse all 3 tiers onto a common Logical Switch and use the NSX Distributed Firewall to manage segmentation and security between VMs.

ECMP, L2VPN and other NSX features may involve changes to the topology depicted above.



## 4. Hardware Requirements

Table 1. NSX Hardware Requirements

	Requirement	Comments
<input type="checkbox"/>	<p>A minimum of one physical server for a Management &amp; Edge Cluster that meets the following specifications:</p> <ul style="list-style-type: none"> <li>• Server hardware is listed on the VMware HCL <sup>1</sup> for vSphere 5.5</li> <li>• 2x Quad Core x86_64 compatible CPUs with a speed of 2Ghz or greater, plus Hardware assisted virtualization support (total of 8 physical cores)</li> <li>• 32GB of RAM or greater</li> <li>• 2x Physical NICs (ideally 4 if 1Gbe NICs are used)</li> <li>• 2x HBAs if FC-SAN is used</li> <li>• Either 5GB of Local Disk/Dedicated boot from SAN LUN or supported ESXi embedded device (USB/SD). Local Disk is not required if vSphere Auto Deploy is used.</li> </ul> <p>If additional management VMs are required (AD/DNS, NTP Syslog etc) these will increase the CPU &amp; Memory requirements. Multiple physical servers may be used to meet the minimum hardware specifications.</p> <p>If sufficient hardware resources are available two Clusters of ESXi hosts can be used for separate Management and Edge clusters. This aligns with a production deployment where the Management Cluster is used to run supporting workloads, but not prepared for NSX Network Virtualization.</p> <p>Also if performance or availability will be tested during the evaluation, the NSX Controller Cluster requires 3 nodes, to comply with the best practice of running each node on a separate server. This means the Management &amp; Edge Cluster will require 3 physical servers.</p>	
<input type="checkbox"/>	<p>A minimum of 2 physical servers for Compute Clusters. To demonstrate the capabilities of network virtualization, VMware recommends allocating 4 servers in two vSphere clusters to the NSX PoC evaluation for Compute Clusters (or more).</p> <p>Sizing of these servers is entirely dependent on the customer workloads used during PoC testing, but the following specifications can be used as a baseline: 2x Quad Core 16GB of RAM per server.</p>	

<sup>1</sup> Refer to <http://www.vmware.com/go/hcl> for the latest VMware HCL information

- 
- Nested ESXi Hypervisors are not supported

---

  - If L2 Bridging to a physical server will be one of the use cases that is evaluated, an additional server is required. Note that L2 Bridging can also be evaluated using a virtual machine connected to a VLAN tagged Portgroup to reduce hardware requirements.

---

  - 300GB of shared storage for Management VMs <sup>2</sup>

---

  - 200GB or greater of shared storage for Customer Workload VMs <sup>3</sup>

---

---

<sup>2</sup> Storage requirements are reduced if thin provisioning is used

<sup>3</sup> Sizing of storage requirements for customer workloads is entirely dependent on the applications, so this is an estimate only

## 5. Software Requirements

Table 2. NSX Software Requirements

	Requirement	Comments
<input type="checkbox"/>	Customer has access to the VMware NSX support portal and has agreed to the relevant VMware Software Agreements and NDA	
<input type="checkbox"/>	Available Perpetual or VSPP vSphere 5.5 licenses (alternatively 60 day evaluations can be used during a PoC).	
<input type="checkbox"/>	<p>The following vSphere 5.5 build versions will be used</p> <ul style="list-style-type: none"> <li>• ESXi 5.5 U2 Build <b>2068190 or later</b></li> <li>• vCenter Server 5.5.0 U2 Build <b>2105955 or later</b></li> <li>• vCenter Server Appliance 5.5.0 U2 GA Build <b>2063318 or later</b></li> </ul> <p>Note: By default the vCenter Server Virtual Appliance will be used for all NSX PoCs</p>	
<input type="checkbox"/>	<p>NSX for vSphere build version:</p> <ul style="list-style-type: none"> <li>• NSX for vSphere 6.1.1 Build <b>2179522</b></li> </ul> <p>Note: NSX Manager is delivered as a Virtual Appliance</p>	
<input type="checkbox"/>	Management host with supported OS & browser combination (as per the product documentation)	
<input type="checkbox"/>	Provide one or more sample VM(s) to be used during the NSX proof of concept. Typically this will be a 2/3-tier application to demonstrate the required networking and security use cases. If customer provided VMs are not available VMware can provide a sample 3-tier application.	

Note that 3<sup>rd</sup> party partner integrations are generally out of scope, unless otherwise agreed to as part of the use cases. These integrated solutions can be evaluated independently from the NSX for vSphere PoC.

VMware vSphere software components should be installed and operational prior to commencing the NSX PoC evaluation. Document the vSphere system details in the following tables:

**Table 3. vCenter Server**

vCenter Server Name	Version	IP Address
	5.5	

**Table 4. ESXi Hosts**

ESXi Hostname	Version	Cluster Name	Datastores	Management IP Address
	5.5			
	5.5			
	5.5			
	5.5			
	5.5			
	5.5			

**Table 5. NSX for vSphere Components**

NSX Component	Version	IP Address
NSX Manager	6.1	
NSX Controller Node 1	6.1	
NSX Controller Node 2	6.1	
NSX Controller Node 3	6.1	
NSX Logical Router Control VMs	6.1	
NSX Edge Services Gateways	6.1	

**Table 6. Management VM Sizing**

VM	vCPU	Memory	Storage	Quantity
vCenter Server Appliance	2	8 Gb	125 Gb	1
NSX Manager	4	12 Gb	60 Gb	1
NSX Controller	4	4 Gb	25 Gb	Typically 3 if evaluating scale out
NSX Edge <small>(Logical Router Control VM size is compact)</small>	1 (compact) 2 (large) 4 (quad-large) 6 (x-large)	512 Mb (compact) 1 Gb (large) 1 Gb (quad-large) 8 Gb (x-large)	512 Mb 512 Mb 512 Mb 4.5 Gb	Dependant on testing requirements/use cases

## 6. Network Requirements

Table 7. NSX Network Requirements

	Requirement	Comments
<input type="checkbox"/>	VLANs for: <ul style="list-style-type: none"> <li>• ESXi Management</li> <li>• VM Management</li> <li>• VXLAN Transport</li> <li>• Routed Datacenter networks used for workloads in PoC evaluation. These can also be isolated if the PoC environment is not connected to external networks.</li> <li>• vMotion (if required)</li> <li>• IP Storage (if required)</li> </ul>	If a L2 network topology is used these VLANs can be shared across clusters. In a L3 topology VLANs are local to the Top of Rack switch.
<input type="checkbox"/>	IP address details for all networks used in the NSX PoC, including: <ul style="list-style-type: none"> <li>- Management and VXLAN transport IPs for ESXi hosts</li> <li>- Static IPs or DHCP reservations on VM management network for vCenter Server, NSX Manager, NSX Controller</li> <li>- Range of IPs on external networks for customer workloads</li> </ul>	
<input type="checkbox"/>	MTU of 1600 or greater on VXLAN transport network(s)	
<input type="checkbox"/>	Optional – for offloading replication of VXLAN frames to the physical network Layer 2 multicast (IGMP snooping & querier) can be configured on physical switches. This is <u>not</u> a requirement in VXLAN deployments with NSX.	
<input type="checkbox"/>	Forward and Reverse DNS resolution for all Management VMs	
<input type="checkbox"/>	NTP Service for time synchronization across Management VMs	
<input type="checkbox"/>	If there is a firewall between management components, the required Ports and Protocols in Table 7 must be permitted. For PoC evaluations it is generally recommended not to implement filtering.	

Document the network parameters for the environment in the following table:

**Table 8. Network Parameters**

Purpose	VLAN ID	Subnet	Gateway
Management & Edge Cluster ESXi Management			
Management & Edge Cluster VM Management			
Management & Edge Cluster vMotion			n/a
Management & Edge Cluster IP Storage			n/a
Management & Edge Cluster VXLAN Transport			
Compute Cluster 1 ESXi Management			
Compute Cluster 1 vMotion			n/a
Compute Cluster 1 IP Storage			n/a
Compute Cluster 1 VXLAN Transport			
Compute Cluster 2 ESXi Management			
Compute Cluster 2 vMotion			n/a
Compute Cluster 2 IP Storage			n/a
Compute Cluster 2 VXLAN Transport			
Any Routed Datacenter networks used for External Access in the PoC evaluation. These can also be isolated if the PoC is not connected to external networks.			
VLAN for physical workloads to be bridged to a logical network in Compute Clusters			n/a

**Table 9. NSX for vSphere Port & Protocol Requirements**

Description	Port(s)	Protocol	Direction
NSX Manager Admin Interface	5480	TCP	Inbound
NSX Manager REST API	443	TCP	Inbound
NSX Manager SSH	22	TCP	Inbound
NSX Manager VIB access	80	TCP	Inbound
NSX Controller SSH	22	TCP	Inbound
NSX Controller REST API	443	TCP	Inbound
NSX Control Plane Protocol (UWA to Controller)	1234	TCP	Inbound
Message bus agent to NSX Manager (AMQP)	5671	TCP	Inbound
NSX Manager vSphere Web Access to vCenter Server	443, 902	TCP	Outbound
NSX Manager to ESXi host	443, 902	TCP	Outbound
VXLAN encapsulation between VTEPs (ESXi hosts on transport network)	8472	UDP	Both
DNS client	53	TCP & UDP	Outbound
NTP client	123	TCP & UDP	Outbound
Syslog (Optional)	514	UDP or TCP	Outbound
ESXi VIB status (to vCenter Server)	80	TCP	Inbound

- This only covers the NSX specific ports and protocols. Refer to the vSphere documentation for ESXi & vCenter Server requirements
- Firewall should also permit established connections between client and server



## 7. Resource Requirements

During a typical NSX for vSphere Proof of Concept, the following customer resources will need to be available during the evaluation. In many cases, multiple roles may be provided by the same individual.

**Table 10. Customer Resources**

	Job Role	Name
<input type="checkbox"/>	vSphere Administrator	
<input type="checkbox"/>	Storage Administrator	
<input type="checkbox"/>	Network Administrator	
<input type="checkbox"/>	Security Administrator	
<input type="checkbox"/>	Cloud/Server Architect	
<input type="checkbox"/>	Network/Security Architect	
<input type="checkbox"/>	Project Executive Stakeholders	
<input type="checkbox"/>	Project Lead/Manager	

**Table 11. VMware Networking & Security Resources (Optional)**

	Job Role	Name
<input type="checkbox"/>	Account Manager	
<input type="checkbox"/>	Systems Engineer	
<input type="checkbox"/>	Post Sales Contact	

## 8. Sample Timeline

A sample timeline for an NSX for vSphere Proof of Concept is provided below. Based on resource availability, complexity of use cases and infrastructure readiness, these timelines can often be reduced (or in large environments may need to be increased).

**Table 12. Timelines**

NSX PoC Timelines
<p><b>Week 1 – Kick Off &amp; Preparation</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Kick off call with team to discuss the PoC requirements, scope and timeframes</li> <li><input type="checkbox"/> Identify key use cases</li> <li><input type="checkbox"/> Update test plan template based on these use cases</li> <li><input type="checkbox"/> Acquire required hardware / software resources</li> <li><input type="checkbox"/> Prepare the physical environment</li> <li><input type="checkbox"/> Install base vSphere software (ESXi and vCenter Server)</li> <li><input type="checkbox"/> Finalize deployment details</li> </ul>
<p><b>Week 2 – NSX Install &amp; Wrap Up</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Install NSX</li> <li><input type="checkbox"/> Execute the tests as per agreed plan</li> <li><input type="checkbox"/> PoC wrap up meeting</li> </ul>