# Recommended Configuration Maximums

NSX for vSphere 6.3

Update 1

Last Updated 7 Nov, 2017

This document supports the version of each product listed and supports all subsequent versions until the document is replaced by a new edition. To check for more recent editions of this document, see <u>VMware Docs</u>

	Recommended	Configu	ıration	Maximum
--	-------------	---------	---------	---------

You can find the most up-to-date technical documentation on the VMware Web site at: http://www.vmware.com/support/

The VMware Web site also provides the latest product updates.

If you have comments about this documentation, submit your feedback to:

docfeedback@vmware.com

Copyright © 2017 VMware, Inc. All rights reserved. Copyright and trademark information.

#### VMware, Inc.

3401 Hillview Ave.

Palo Alto, CA 94304

www.vmware.com

## **Contents**

Contents	3
Updated Information	4
1 Introduction	5
2 General	6
Nodes	6
Edge Service Gateway	7
3 Layer 2 Networking	8
4 Layer 3 Networking	9
DHCP	9
Distributed Logical Router	10
Edge Service Gateway Layer 3	11
5 Firewall	14
Distributed Firewall	14
Edge Service Gateway Firewall	15
Identity Firewall	16
6 Load Balancing	17
7 VPN	18
Layer 2 VPN	18
IPsec VPN	19
SSL VPN	20

## **Updated Information**

This *Recommended Configuration Maximums* document is updated when necessary, which is typically with each major or minor release of the product.

This table provides the update history of the *Recommended Configuration Maximums*.

Update	Description
1. 7 Nov, 2017	Initial release for NSX for vSphere version 6.3.3 and later.

#### 1 Introduction

This document provides the recommended configuration maximums for NSX for vSphere. Please consider the following when you use this document to design, deploy and operate the product.

- When you select and configure your virtual and physical equipment, it is highly recommended
  that you stay at or below the maximums supported by NSX for vSphere as described in this
  document.
- The limits presented in the following sections represent tested, recommended limits, and are fully supported by VMware.
- The limits presented in the guide are applicable to NSX for vSphere. The limits can be affected
  by other factors, such as hardware dependencies. For more information about supported
  hardware, see the appropriate NSX for vSphere installation and administration guide. Consult
  individual solution limits to ensure that you do not exceed supported configurations for your
  environment.
- It may not be possible to maximize all configuration settings and expect your desired outcome.
- The recommended configuration maximums do not represent the theoretical possibilities of NSX for vSphere scale.

### 2 General

#### **Nodes**

NSX for vSphere has a number of component nodes required for operation of the product. These include the NSX Manager, NSX Controllers and Hosts that are prepared for NSX. This section captures the configuration maximums for NSX nodes. In addition, NSX supports some vCenter objects that are discovered from vCenter inventory. The configuration maximums for these objects are listed in this section.

Table 2-1. Node Maximums

Item	Recommended Maximum
vCenter systems in single NSX Manager deployments	1
vCenter systems in Cross-vCenter deployments	8
NSX Controllers	3 Only 3 controllers are supported in a production deployment of NSX for vSphere. A single controller may be used in a lab or proof-of-concept deployment but is not supported for production deployments.
vCenter Clusters	64
Hosts per Cluster	64
Hosts per NSX Manager (single vCenter / Transport Zone)	512 For IDFW deployments, see the IDFW section of this document.
Hosts in a Cross-vCenter deployment	1,024 For IDFW deployments, see the IDFW section of this document.

#### **Edge Service Gateway**

A core component of NSX for vSphere is the Edge Service Gateway, which delivers routing, load-balancing, VPN and other features. There are several general configuration maximums that are covered in this section. Configuration maximums of services delivered by the Edge are covered in subsequent sections.

Table 2-2. General Edge Service Gateway Maximums

Item	Recommended Maximum
Edge Service Gateways per NSX Manager	2,000 The backup Edge in a High-Availability pair of Edges is not included in this maximum.
Interfaces	10 Includes internal, uplink and trunk.
Subinterfaces per Edge	200

## 3 Layer 2 Networking

NSX for vSphere offers a layer 2 overlay networking solution as well as layer 2 bridging. The configuration maximums of these layer 2 features are listed in this section.

Table 3-1. Layer 2 Maximums

Item	Recommended Maximum
Logical Switches	10,000
Logical Switch Ports	20,000
Universal Logical Switches in a Cross-vCenter deployment	8,500 This maximum includes both universal and non-universal logical switches.
VXLAN/VLAN Bridging per Distributed Logical Router instance	500

## 4 Layer 3 Networking

#### **DHCP**

NSX for vSphere provides a DHCP server to deliver IP addresses to DHCP clients. This section covers configuration maximums for the DHCP service.

**Table 4-1.** DHCP Maximums

Item	Recommended Maximum
DHCP Pools per Edge Service Gateway	20,000 Applies to all Edge sizes.

#### **Distributed Logical Router**

NSX for vSphere provides an in-kernel distributed logical router. This section covers configuration maximums for the distributed logical router.

Table 4-2. Distributed Logical Router Maximums

Item	Recommended Maximum
Distributed Logical Routers	1,000
Distributed Logical Router interfaces per Distributed Logical Router	999 Maximum of 8 uplinks.
Distributed Logical Router interfaces per ESXi Host	10,000
ARP entries per Distributed Logical Router	20,000 If this number of ARP entries is exceeded, newer ARP entries in the ARP table will replace older entries.
Routes per Distributed Logical Router	2,000 Includes connected routes. Maximum 750 LSA type-1 prefixes.
OSPF Adjacencies per Distributed Logical Router	10
BGP Neighbors per Distributed Logical Router	10

#### **Edge Service Gateway Layer 3**

The NSX for vSphere Edge Service Gateway provides a number of layer 3 networking features, such as static and dynamic routing. The configuration maximums for this Edge Service Gateway based routing is listed in this section.

**Table 4-3.** Edge Service Gateway Layer 3 Maximums

Item	Recommended Maximum
ECMP Paths	8
NAT Rules per Edge Service Gateway - Compact Edge size	2,048 Includes both SNAT and DNAT rules.
NAT Rules per Edge Service Gateway - Large Edge size	4,096 Includes both SNAT and DNAT rules.
NAT Rules per Edge Service Gateway - Quad Large Edge size	4,096 Includes both SNAT and DNAT rules.
NAT Rules per Edge Service Gateway - Extra Large Edge size	8,192 Includes both SNAT and DNAT rules.
Static Routes per Edge Service Gateway	2,048 Applies to all Edge sizes.
BGP Routes per Edge Service Gateway - Compact Edge size	20,000
BGP Routes per Edge Service Gateway - Large Edge size	50,000
BGP Routes per Edge Service Gateway - Quad Large Edge size	250,000
BGP Routes per Edge Service Gateway - Extra Large Edge size	250,000
BGP Neighbors per Edge Service Gateway - Compact Edge size	10
BGP Neighbors per Edge Service Gateway - Large Edge size	20
BGP Neighbors per Edge Service Gateway - Quad Large Edge size	50
BGP Neighbors per Edge Service Gateway - Extra Large Edge size	50
OSPF LSA entries per Edge Service Gateway - Compact Edge size	20,000 Maximum of 750 type-1 LSA entries.

OSPF LSA entries per Edge Service Gateway - Large Edge size	50,000 Maximum of 750 type-1 LSA entries.
OSPF LSA entries per Edge Service Gateway - Quad Large Edge size	100,000 Maximum of 750 type-1 LSA entries.
OSPF LSA entries per Edge Service Gateway - Extra Large Edge size	100,000 Maximum of 750 type-1 LSA entries.
OSPF Adjacencies per Edge Service Gateway - Compact Edge size	10
OSPF Adjacencies per Edge Service Gateway - Large Edge size	20
OSPF Adjacencies per Edge Service Gateway - Quad Large Edge size	40
OSPF Adjacencies per Edge Service Gateway - Extra Large Edge size	40
OSPF Routes Redistributed per Edge Service Gateway - Compact Edge size	2,000
OSPF Routes Redistributed per Edge Service Gateway - Large Edge size	5,000
OSPF Routes Redistributed per Edge Service Gateway - Quad Large Edge size	20,000
OSPF Routes Redistributed per Edge Service Gateway - Extra Large Edge size	20,000
Total Routes per Edge Service Gateway - Compact Edge size	20,000
Total Routes per Edge Service Gateway - Large Edge size	50,000
Total Routes per Edge Service Gateway - Quad Large Edge size	250,000
Total Routes per Edge Service Gateway - Extra Large Edge size	250,000
ARP entries per Edge Service Gateway - Compact Edge size	1,024 If exceeded, newer ARP entries in the ARP table will replace older entries.
ARP entries per Edge Service Gateway - Large Edge size	2,048 If exceeded, newer ARP entries in the ARP table will replace older entries.
ARP entries per Edge Service Gateway - Quad Large Edge size	2,048 If exceeded, newer ARP entries in the ARP table will replace older entries.

ARP entries per Edge Service Gateway - Extra Large Edge size	2,048 If exceeded, newer ARP entries in the ARP table will replace older entries.
--------------------------------------------------------------	-----------------------------------------------------------------------------------

## **5 Firewall**

#### **Distributed Firewall**

NSX for vSphere provides a distributed, in-kernel Host based firewall to achieve micro-segmentation of workloads at the virtual NIC level. The configuration maximums of the distributed firewall are covered in this section.

Table 5-1. Distributed Firewall Maximums

Item	Recommended Maximum
Rules per NSX Manager	100,000 Can be a mix of local and universal rules.
Rules per Virtual NIC	3,500
Distributed Firewall Sections	10,000
Security Groups per NSX Manager	10,000
Audit Log entries	1,000,000
Flow Monitoring Data	2,000,000 Records over 15 days.
Distributed Firewall Rule Configurations	100
Universal Distributed Firewall Rules	24,000
Universal Firewall Sections	500
Universal Security Groups	4,000
Universal IP Sets	4,000
Universal IP Sets per Universal Security Group	10
Universal Security Tags	750
Universal Security Tags per Virtual Machine	5

### **Edge Service Gateway Firewall**

The NSX for vSphere Edge Service Gateway can function as a firewall in addition to the distributed firewall. This section covers configuration maximums of the Edge Service Gateway firewall.

 Table 5-2. Edge Service Gateway Firewall Maximums

Item	Recommended Maximum
Firewall Rules per Edge Service Gateway	2,000 Applies to all Edge sizes

#### **Identity Firewall**

NSX for vSphere supports an identity-based firewall in which the firewall rules that protect a given workload can be changed based on the identity of the user of the workload. This section covers the configuration maximums of the identity firewall.

**Table 5-3.** Identity Firewall Maximums

Item	Recommended Maximum
Active Directory groups	30,000
Users per Active Directory group	250
Users in the Active Directory Domain	100,000
Virtual Machines joined to the Active Directory Domain	2,500
Groups per individual user	20
Security Groups based on Active Directory	300
Active Directory Groups per Security Group	10
Virtual Machines per Security Group	1,000
Security Policies	250
Hosts	250 For the Identity Firewall Use Case
Virtual Machines per Host	50

## 6 Load Balancing

The NSX for vSphere Edge Service Gateway provides a load balancing service to distribute load across multiple workloads. This section covers the configuration maximums for the load balancing feature of NSX.

Table 6-1. Load Balancer Maximums

Item	Recommended Maximum
Load Balancer VIPs per Edge Service Gateway - Compact Edge size	64
Load Balancer VIPs per Edge Service Gateway - Large Edge size	64
Load Balancer VIPs per Edge Service Gateway - Quad Large Edge size	64
Load Balancer VIPs per Edge Service Gateway - Extra Large Edge size	1,024
Load Balancer Pools per Edge Service Gateway - Compact Edge size	64
Load Balancer Pools per Edge Service Gateway - Large Edge size	64
Load Balancer Pools per Edge Service Gateway - Quad Large Edge size	64
Load Balancer Pools per Edge Service Gateway - Extra Large Edge size	1,024
Load Balancer Servers per Pool - Compact Edge size	320
Load Balancer Servers per Pool - Large Edge size	320
Load Balancer Servers per Pool - Quad Large Edge size	320
Load Balancer Servers per Pool - Extra Large Edge size	3,072
Load Balancer Application Rule size in Characters	4,096 Applies to all Edge sizes

#### 7 VPN

### Layer 2 VPN

The NSX for vSphere Edge Service Gateway provides a layer 2 VPN service. This section covers the configuration maximums for the layer 2 VPN feature of NSX.

**Table 7-1.** Layer 2 VPN Maximums

Item	Recommended Maximum
L2VPN clients (spoke) handled by a single L2VPN server (hub)	5
Networks per L2VPN client/server pair	200

#### **IPsec VPN**

The NSX for vSphere Edge Service Gateway provides an IPsec VPN service. This section covers the configuration maximums for the IPsec VPN feature of NSX.

Table 7-2. IPsec VPN Maximums

Item	Recommended Maximum
IPsec Tunnels per Edge Service Gateway - Compact Edge size	512
IPsec Tunnels per Edge Service Gateway - Large Edge size	1,600
IPsec Tunnels per Edge Service Gateway - Quad Large Edge size	4,096
IPsec Tunnels per Edge Service Gateway - Extra Large Edge size	6,000

#### **SSL VPN**

The NSX for vSphere Edge Service Gateway provides an SSL VPN service. This section covers the configuration maximums for the SSL VPN feature of NSX.

**Table 7-3.** SSL VPN Maximums

Item	Recommended Maximum
Concurrent Sessions - Compact Edge size	50
Concurrent Sessions - Large Edge size	100
Concurrent Sessions - Quad Large Edge size	100
Concurrent Sessions - Extra Large Edge size	1,000
Private Networks	16 Applies to all Edge sizes